



FOURSTROKE®

6 - 2.5 HP

Models ¹	6 FourStroke	5 FourStroke Sailpower	5 FourStroke	4 FourStroke	3.5 FourStroke	2.5 FourStroke
Kilowatts ²	4.4	3.7	3.7	2.9	2.6	2
Max.RPM at Full Throttle	5000-6000	4500-5500	4500-5500	4500-5500	5000-6000	4500-5500
Cylinders	1	1	1	1	1	1
Smart Craft Compatible	N/A	N/A	N/A	N/A	N/A	N/A
Displacement	123 cc	123 cc	123 cc	123 cc	85 cc	85 cc
Starting	Manual	Manual	Manual	Manual	Manual	Manual
Gear Ratio	2.15:1	2.15:1	2.15:1	2.15:1	2.15:1	2.15:1
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N	F-N
Steering Midsection	Tiller -RO	Tiller -RO	Tiller -RO	Tiller -RO	Tiller	Tiller
Alternator System	OPT	4 amp (50 W)	4 amp (50 W) ML	OPT	N/A	N/A
Fuel System	CARB	CARB	CARB	CARB	CARB	CARB
Trim Positions	6 & SWD	6 & SWD	6 & SWD	6 & SWD	4	4
Fuel Tank	1.1 L INT - RO	1.1 L INT - RO	1.1 L INT - RO	1.1 L INT - RO	0.95 litre INT	0.95 litre INT
Fuel Requirements ³	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R
Weight ⁴	25 kg	27 kg	25 kg	25 kg	17 kg	17 kg
Available Boat Transom Heights	S - L	S - L	S - L - XL	S - L	S - L	S
Counter Rotation	N/A	N/A	N/A	N/A	N/A	N/A

¹ Model offering may vary from one country to another. Please see your local dealer for specific information.² Hp/KW measured at propshaft in accordance with ICOMIA 28.

OPTIMAX®

200 HP



FOURSTROKE®

80 - 25 HP

OptiMax Sportjet 200	80 EFI Jet	65 EFI Jet	40 EFI Jet	25 EFI Jet
147	59	48	29.4	18.4
5150-5650	5000-6000	5000-6000	5000-6000	5000-5500
V-6	4 (in-line)	4 (in-line)	4 (in-line)	3 (in-line)
YES	YES	YES	YES	N/A
2507 cc	2064 cc	2064 cc	995 cc	526
Electric	Electric	Electric	Electric	Manual and Electric
1.25:1	Jet drive	Jet drive	Jet drive	Jet drive
F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Remote	Remote - BTO	Remote - BTO	Remote - BTO	Tiller or Remote
60 amp (756 W)	35 amp (441 W)	35 amp (441 W)	18 amp (226 W)	15 amp (186 W)
DFI	EFI	EFI	EFI	EFI
N/A	EHPT	EHPT	GAT	GAT
N/A	N/A	N/A	N/A	25 L
UL95R	UL95R	UL95R	UL95R	UL95R
166 kg	165 kg	165 kg	121 kg	84 kg
JET	L	L	S	S
N/A	N/A	N/A	N/A	N/A

³ 90RON compatible⁴ Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller.GEAR SHIFT **DT**S: Digital Throttle and Shift • **F-N-R**: Mechanical Forward Neutral Reverse • **F-N**: Forward NeutralSTEERING MIDSECTION **AMS**: Advanced Mid Section • **CMS**: Conventional Mid Section • **EHPS**: Electric Hydraulic Power Steering • **BTO**: Big Tiller Optional • **RO**: Remote optionalALTERNATOR SYSTEM **ESM**: On Electric Start Models only • **OPT**: Optional • **OPT**: Optional 4 amp (50 W) lighting, 2 amp (25 W) charging • **ML**: ML Models onlyFUEL SYSTEM **EFI**: Electronic Fuel Injection • **Sci**: Super Charge Injection • **DFI**: Direct Fuel Injection • **CARB**: through carburetorTRIM SYSTEM **EHPT**: Electric Hydraulic Power Trim and Tilt • **EHT**: Electric Hydraulic Tilt (no Trim) • **GAT**: Gas assist trim • **MTT**: Manual Trim and Tilt • **SWD**: Shallow Water driveFUEL TANK **INT**: Integrated fuel tank • **RO**: remote optional

AVAILABLE BOAT TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)

COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)

**FOURSTROKE®**
30 - 25 HP**FOURSTROKE®**
20 - 15 HP**FOURSTROKE®**
9.9 - 8 HP

Models ¹	30 EFI	30 EFI	25 EFI	20 EFI	15 EFI ProKicker	15 EFI	9.9 FourStroke	9.9 FourStroke CT	8 FourStroke
Kilowatts ²	22.1	18.4	18.4	14.7	11.0	11.0	7.3	7.3	5.9
Max.RPM at Full Throttle	5250-6250	5000-6000	5000-5500	5700-6200	5700-6200	5700-6200	5000-6000	5000-6000	5000-6000
Cylinders	3 (in-line)	3 (in-line)	3 (in-line)	2 (in-line)	2 (in-line)	2 (in-line)	2 (in-line)	2 (in-line)	2 (in-line)
Smart Craft Compatible	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Displacement	526 cc	526 cc	526 cc	333 cc	333 cc	333 cc	208 cc	208 cc	208 cc
Starting	Manual and Electric	Manual and Electric	Manual and Electric	Manual or Electric	Manual	Manual or Electric	Manual or Electric	Manual or Electric	Manual or Electric
Gear Ratio	1.92:1	1.92:1	Jet drive	2.15:1	2.15:1	2.15:1	2.08:1	2.42:1	2.08:1
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Steering Midsection	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote
Alternator System	15 amp (186 W)	15 amp (186 W)	15 amp (186 W)	12 amp (145 W)	12 amp (145 W)	12 amp (145 W)	6 amp (76 W) ESM	6 amp (76 W) ESM	6 amp (76 W) ESM
Fuel System	EFI	EFI	EFI	EFI	EFI	EFI	CARB	CARB	CARB
Trim Positions	EHPT or GAT or MTT	EHPT or MTT	GAT	6 & SWD or EHT	6 & SWD or EHT	6 & SWD or EHT	6 & SWD or EHT	6 & SWD or EHT	6 & SWD
Fuel Tank	25 L	25 L	25 L	12 L	12 L	12 L	12 L	12 L	12 L
Fuel Requirements ³	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R
Weight ⁴	78 kg	71 kg	84 kg	45 kg	56 kg	45 kg	38 kg	40 kg	38 kg
Available Boat Transom Heights	S - L	S - L	S	S - L	S - L	S - L	S - L	S - L	S - L
Counter Rotation	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

¹ Model offering may vary from one country to another. Please see your local dealer for specific information.² Hp/KW measured at propshaft in accordance with ICOMIA 28.³ 90RON compatible⁴ Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller.**GEAR SHIFT** **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral**STEERING MIDSECTION** **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section • **EHPS:** Electric Hydraulic Power Steering • **BTO:** Big Tiller Optional • **RO:** Remote optional**ALTERNATOR SYSTEM** **ESM:** On Electric Start Models only • **OPT:** Optional • **OPT:** Optional 4 amp (50 W) lighting, 2 amp (25 W) charging • **ML:** ML Models only**FUEL SYSTEM** **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection • **DFI:** Direct Fuel Injection • **CARB:** through carburetor**TRIM SYSTEM** **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **MTT:** Manual Trim and Tilt • **SWD:** Shallow Water drive**FUEL TANK** **INT:** Integrated fuel tank • **RO:** remote optional**AVAILABLE BOAT TRANSOM HEIGHTS** 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)**COUNTER ROTATION** 635 mm(CXL) - 762 mm(CXXL)



PRO XS®

115 HP



FOURSTROKE®

115 - 80 HP



FOURSTROKE®

60 - 40 HP

Models ⁽¹⁾	115 Pro XS	115 Pro XS CT	115 EFI	115 EFI CT	100 EFI	100 EFI CT	80 EFI	60 EFI CT	60 EFI	50 EFI	40 EFI	40 EFI	40 PRO EFI	40 Carb
Kilowatts ²	85	85	85	85	74	74	59	44	44	37	29.4	29.4	29.4	29.4
Max.RPM at Full Throttle	5300-6300	5300-6300	5000-6000	5000-6000	5000-6000	5000-6000	4500-5500	5500-6000	5500-6000	5500-6000	5500-6000	5500-6000	5500-6000	5500-6000
Cylinders	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	4 (in-line)	3 (in-line)	4 (in-line)	3 (in-line)
Smart Craft Compatible	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Displacement	2064 cc	2064 cc	2064 cc	2064 cc	2064 cc	2064 cc	2064 cc	995 cc	995 cc	995 cc	995 cc	747 cc	995 cc	747 cc
Starting	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Manual
Gear Ratio	2.07:1	2.38:1	2.07:1	2.38:1	2.07:1	2.38:1	2.07:1	2.33:1	1.83:1	1.83:1	1.83:1	2.00:1	2.33:1	2.00:1
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Steering Midsection	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Remote - BTO	Tiller or Remote
Alternator System	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)	18 amp (226 W)	18 amp (226 W)	18 amp (226 W)	18 amp (226 W)	18 amp (226 W)	18 amp (226 W)	18 amp (226 W)
Fuel System	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	CARB
Trim Positions	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT	EHPT or GAT or MTT	EHPT	GAT
Fuel Tank	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Fuel Requirements ³	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R	UL95R
Weight ⁴	163 kg	165 kg	163 kg	165 kg	163 kg	165 kg	163 kg	118 kg	112 kg	112 kg	112 kg	98 kg	112 kg	93 kg
Available Boat Transom Heights	L - XL	L - XL	L - XL	L - XL	L - XL	L - XL	L - XL	L	L	L	L	S - L	L	S-L
Counter Rotation	N/A	N/A	N/A	CXL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

¹ Model offering may vary from one country to another. Please see your local dealer for specific information.² Hp/KW measured at propshaft in accordance with ICOMIA 28.³ 90RON compatible⁴ Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller.GEAR SHIFT **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward NeutralSTEERING MIDSECTION **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section • **EHPS:** Electric Hydraulic Power Steering • **BTO:** Big Tiller Optional • **RO:** Remote optionalALTERNATOR SYSTEM **ESM:** On Electric Start Models only • **OPT:** Optional • **OPT:** Optional 4 amp (50 W) lighting, 2 amp (25 W) charging • **ML:** ML Models onlyFUEL SYSTEM **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection • **DFI:** Direct Fuel Injection • **CARB:** through carburetorTRIM SYSTEM **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **MTT:** Manual Trim and Tilt • **SWD:** Shallow Water driveFUEL TANK **INT:** Integrated fuel tank • **RO:** remote optional

AVAILABLE BOAT TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)

COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)