

Mercury Outboard Motor Specification

Model: Four Stroke 2.5hp EFI

Built to deliver the type of power, thrust, and control that wider, heavier boats require.

HP / kW	<ul style="list-style-type: none">• 2.5 / 1.9
Engine type	<ul style="list-style-type: none">• 1 cylinder
Displacement (CID/CC)	<ul style="list-style-type: none">• 5.2 / 85
Full throttle RPM	<ul style="list-style-type: none">• 4500-5500
Fuel induction system	<ul style="list-style-type: none">• 2-valve pushrod (overhead valve)
Recommended fuel	<ul style="list-style-type: none">• Unleaded 90RON minimum
Recommended oil	<ul style="list-style-type: none">• Mercury FourStroke Oil 10W-30
Engine protection operator warning system	<ul style="list-style-type: none">• Over-rev
Starting	<ul style="list-style-type: none">• Manual
Steering	<ul style="list-style-type: none">• Tiller with 360° turning
Shaft length	<ul style="list-style-type: none">• 15" / 381 mm
Gearcase ratio	<ul style="list-style-type: none">• 2.15:1
Dry weight *Lightest model available	<ul style="list-style-type: none">• 41 lbs / 18 kg
CARB star rating	<ul style="list-style-type: none">• 3
Bore and stroke	<ul style="list-style-type: none">• 2.16 x 1.42" / 55 x 36 mm
Ignition	<ul style="list-style-type: none">• CDI w/electronic spark advance
Fuel system	<ul style="list-style-type: none">• Carbureted
Cooling system	<ul style="list-style-type: none">• Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none">• F-N
Gearcase options	<ul style="list-style-type: none">• Standard
Trim system	<ul style="list-style-type: none">• 4 position
Trim positions	<ul style="list-style-type: none">• 4
Exhaust system	<ul style="list-style-type: none">• Above prop
Shallow water trim range (degrees)	<ul style="list-style-type: none">• 16
Color	<ul style="list-style-type: none">• Phantom Black