

2.5-20HP

FOURSTROKE SPECIFICATIONS



HP	2.5	3.5	4	5	6
WOT RPM:	4500-5500	5000-6000	4500-5500	4500-5500	5000-6000
Engine Type:	1 cylinder	1 cylinder	1 cylinder	1 cylinder	1 cylinder
Displacement:	85cc (5.2 cu in)	85cc (5.2 cu in)	123cc (7.5 cu in)	123cc (7.5 cu in)	123cc (7.5 cu in)
Induction:	2-valve, pushrod	2-valve, pushrod	2-valve, pushrod	2-valve, pushrod	2-valve, pushrod
Starting:	Manual	Manual	Manual	Manual	Manual
Gear Ratio:	2.15:1	2.15:1	2.15:1	2.15:1	2.15:1
Alternator:	N/A	N/A	N/A	Self Power 4 amp (50 watt)	N/A
Trim System:	4-position manual	4-position manual	6-position manual w/ shallow-water drive	6-position manual w/ shallow-water drive	6-position manual w/ shallow-water drive
Dry Weight:	41lbs (18kg)	41lbs (18kg)	57lbs (26kg)	57lbs (26kg)	57lbs (26kg)
Steering:	360° Tiller	360° Tiller	Tiller	Tiller	Tiller
Shaft Length:	15 in (381mm)	15 in (381mm) 20 in (508mm)	15 in (381mm) 20 in (508mm)	15 in (381mm) 20 in (508mm) 25 in (635mm)	15 in (381mm) 20 in (508mm)