



## **Mercury Outboard Motor Specification**

## Model: Four Stroke 5hp EFI

Multiple trim positions enable fine tuning and shallow water running. A through prop exhaust makes it extremely quiet.

HP/kW

**Engine type** 

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Recommended fuel

Recommended oil

Engine protection operator warning system

Starting

Steering

Shaft length

Gearcase ratio

Dry weight \*Lightest model available

CARB star rating

Bore and stroke

Ignition

Fuel system

Cooling system

Gear shift

Gearcase options

**Trim positions** 

**Exhaust system** 

Shallow water drive

Shallow water trim range (degrees)

Integrated fuel tank (gal / L)

Optional fuel tank (gal / L)

Color

- 5/3.7
- 1 cylinder
- 7.5 / 123
- 4500-5500
- 2-valve pushrod (overhead valve)
- Unleaded 90RON minimum
- Mercury Four Stroke Oil 10W-30
- Low oil pressure
- Over-rev
- Manual
- Tiller
- 15"/381 mm
- 25" / 635 mm
- 2.15:1
- 25 kg
- 3
- 2.32 x 1.77" / 59 x 45 mm
- CDI w/electronic spark advance
- Carbureted
- Water-cooled with thermostat
- F-N-R
- Standard
- 6
- Through prop
- Yes
- 16
- 0.3 / 1.1
- 3.2 / 12
- Phantom Black