



Mercury Outboard Motor Specification

Model: Four Stroke 8hp EFI

Enhancements include simplified starting procedure, faster warmup and better idle run quality.

HP/kW

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt Recommended fuel Recommended oil

Engine protection operator warning

system Starting

Steering Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition
Fuel system
Cooling system
Gear shift

Gearcase options
Trim positions
Exhaust system
Shallow water drive

Shallow water trim range (degrees) Remote fuel tank standard (gal / L)

Color

8/5.9

• Inline 2

• 12.8 / 208

5000-6000

 2 valves per cylinder, single overhead cam (SOHC)

• 6 amp / 76 watt

• Unleaded 90RON minimum

Mercury FourStroke Oil 10W-30

Low oil pressure

Over-rev

Electric

Manual

Tiller

• 15" / 381 mm

• 20" / 508 mm

2.08:1

38 kg

• 3

• 2.16 x 1.73" / 55 x 44 mm

CDI w/electronic spark advance

Carbureted

Water-cooled with thermostat

• F-N-R

Standard

Ratcheting

Through prop

Yes

• 16

• 3.2 / 12

Phantom Black