



Mercury Outboard Motor Specification

Model: Four Stroke 9.9hp EFI

Built to deliver the type of power, thrust, and control that wider, heavier boats require.

HP	/	ΚW
----	---	----

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt Recommended fuel

Recommended oil

Engine protection operator warning

system

Starting

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition

Fuel system

Cooling system

Gear shift

Gearcase options

Trim system

Trim positions

Exhaust system

Shallow water drive

Shallow water trim range (degrees)

Remote fuel tank standard (gal / L)

Color

- 9.9 / 7.3
- Inline 2
- 12.8 / 208
- 5000-6000
- 2 valves per cylinder, single overhead cam (SOHC)
- 6 amp / 76 watt
- Unleaded 90RON minimum
- Mercury FourStroke Oil 10W-30
- Low oil pressure
- Over-rev
- Electric
- Manual
- Remote
- Tiller
- 15" / 381 mm
- 20" / 508 mm
- 2.08:1
- 38 kg
- 3
- 2.16 x 1.73" / 55 x 44 mm
- CDI w/electronic spark advance
- Carbureted
- Water-cooled with thermostat
- F-N-R
- Standard
- Power Tilt
- Ratcheting
- Through prop
- Yes
- 16
- 3.2 / 12
- Phantom Black