



Mercury Outboard Motor Specification

Model: Four Stroke 15hp EFI

Low weight and strong torque provides best in class acceleration and top speed

ш	Ρ,	/ I		۱٨	•
П	г,	/	Ν,	V	v

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt

Recommended fuel

Recommended oil

Engine protection operator warning

system

Starting

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating

Bore and stroke

Ignition

Fuel system

Cooling system

Gear shift

Gearcase options

Trim system

Trim positions

Exhaust system

Shallow water drive

Shallow water trim range (degrees)

Remote fuel tank (optional)

Remote fuel tank standard (gal / L)

Color

- 15/11.1
- Inline 2
- 20.3 / 333
- 5700 6200
- 2 valves per cylinder, single overhead cam (SOHC)
- 12/145 electric
- 87 octane compatible (up to 10% ethanol)
- 25W-40 Synthetic Blend
- Mercury FC-W 10W-30 4-Stroke Marine Oil
- Low oil pressure
- Over-rev
- Overheat
- Sensor failure
- Electric
- Manual
- Remote
- Tiller
- 15" / 381 mm
- 20" / 508 mm
- 2.15:1
- 99 lbs / 45 kg
- 3
- 2.40 x 2.24" / 61 x 57 mm
- CDI w/electronic spark advance
- Electronic Fuel Injection (EFI)
- Water-cooled with thermostat
- F-N-R
- Standard
- Manual
- Power Tilt
- 6
- Through prop
- Yes
- 16
- Yes
- 3.2 / 12
- Phantom Black