



Mercury Outboard Motor Specification

Model: Four Stroke 20hp EFI

Ultralightweight and reliable, with little vibration.

HP / kW

• 20 / 14.7

Engine type

• Inline 2

Displacement (CID/CC)

• 20.3 / 333

• 5700 - 6200

Fuel induction system

• Single Overhead Cam

Alternator amp / Watt

• 12/145 electric

• 87 octane / up to 10% ethanol

Recommended oil
 25W-40 Synthetic Blend
 Mercury FC-W 10W-30 4-Stroke Marine Oil

Engine protection operator warning system • Low oil pressure

Over-revOverheatSensor failure

Tiller

Starting

• Electric

• Manual

Steering

• Remote

Shaft length• 15"/381 mm
• 20"/508 mm

Gearcase ratio • 2.15:1

Dry weight *Lightest model available • 99 lbs / 45 kg

CARB star rating

• 3

Bore and stroke

• 2.40 x 2.24" / 61 x 57 mm

 Ignition
 • CDI w/electronic spark advance

 Fuel system
 • Electronic Fuel Injection (EFI)

 Cooling system
 • Water-cooled with thermostat

Gear shift

F-N-R

Gearcase options

Trim system

Manual
Power Tilt

Trim positions

Exhaust system

Shallow water drive

Shallow water trim range (degrees)

6

Through prop

Yes

16

Color • Phantom Black

Remote fuel tank standard (gal / L)

3.2 / 12