



## **Mercury Outboard Motor Specification**

## Model: Four Stroke 25hp EFI

Delivers consistent, easy starting, crisp throttle response, increased fuel economy, and outstanding overall performance.

HP/kW
-------

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt Recommended fuel Recommended oil

Engine protection operator warning

system

Starting

Steering

Shaft length

Gearcase ratio

Dry weight \*Lightest model available

CARB star rating Bore and stroke

Ignition
Fuel system
Cooling system
Gear shift

Gearcase options

Trim system

Exhaust system

Shallow water trim range (degrees) Remote fuel tank standard (gal / L)

Color

- 25 / 18.6
- Inline 3
- 32.1/526
- 5000-6000
- 2 valves per cylinder, single overhead cam (SOHC)
- 15 amp / 186 watt
- Unleaded 90RON minimum
- Mercury Four Stroke Oil 10W-30
- Low oil pressure
- Over-rev
- Overheat
- Sensor failure
- Electric (turn-key)
- Manual
- Remote
- Tiller
- 15" / 381 mm
- 20" / 508 mm
- 1.92:1
- 71 kg
- 3
- 2.40 x 2.36" / 61 x 60 mm
- CDI w/electronic spark advance
- Electronic Fuel Injection (EFI)
- Water-cooled with thermostat
- F-N-R
- Standard
- Manual
- Power Trim
- Through prop
- 16
- 6.6 / 25
- Phantom Black