



Mercury Outboard Motor Specification

Model: Four Stroke 30hp EFI

Enhanced fuel injection (EFI) for boosted efficiency and low-end torque for excellent acceleration.

HP/kW

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt Recommended fuel Recommended oil

Engine protection operator warning

system

Starting

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition

Fuel system
Cooling system

Gear shift

Gearcase options

Trim system

Exhaust system

Shallow water trim range (degrees) Remote fuel tank standard (gal / L)

Color

• 30 / 22.4

Inline 3

32.1/526

5250-6250

 2 valves per cylinder, single overhead cam (SOHC)

• 15 amp / 186 watt

• Unleaded 90RON minimum

• Mercury Four Stroke Oil 10W-30

Low oil pressure

Over-rev

Overheat

Sensor failure

Electric (turn-key)

Manual

Remote

Tiller

• 15" / 381 mm

• 20" / 508 mm

• 1.92:1

• 78 kg

• 3

• 2.40 x 2.36" / 61 x 60 mm

CDI w/electronic spark advance

• Electronic Fuel Injection (EFI)

Water-cooled with thermostat

• F-N-R

Standard

Gas assist

Power Trim

Through prop

• 16

6.6 / 25

Phantom Black