



Mercury Outboard Motor Specification

Model: Four Stroke 40hp EFI

For reliable turnkey starts, improved fuel efficiency and instant throttle response.

HP/kW

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt Recommended fuel Recommended oil

Engine protection operator warning system

Compatible with SmartCraft digital technology

Starting

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition

Fuel system

Cooling system

Gear shift

Gearcase options

Trim system

Exhaust system

Shallow water trim range (degrees)

Remote fuel tank (optional)

Color

Lubrication system

- 40/30
- Inline 3
- 45.6 / 747
- 5500-6000
- 2 valves per cylinder, single overhead cam (SOHC)
- 18 amp / 226 watt
- 87 octane / up to 10% ethanol
- Mercury FourStroke 25W40 Marine Oil
- Low oil pressure
- Over-rev
- Overheat
- Yes
- Electric (turn-key)
- Remote
- Tiller
- 15" / 381 mm
- 20" / 508 mm
- 2.00:1
- 204 lbs / 93 kg
- 3
- 2.56 x 2.95" / 65 x 75 mm
- ECM 70
- Electronic Fuel Injection (EFI)
- Water-cooled with thermostat
- F-N-R
- Standard
- Gas assist
- Power Tilt
- Power Trim
- Through prop
- 20
- Yes
- Phantom Black
- Wet sump