



Mercury Outboard Motor Specification

Model: Four Stroke 50hp EFI

Delivers more low-end torque for excellent acceleration, even when pushing a heavy load.

HP/kW

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt

Recommended fuel

Recommended oil

Engine protection operator warning

system

Compatible with SmartCraft digital

technology Starting

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating

Bore and stroke

Ignition

Fuel system

Cooling system

Gear shift

Gearcase options

Trim system

Exhaust system

Shallow water trim range (degrees)

Remote fuel tank (optional)

Color

Lubrication system

- 50/37
- Inline 4
- 60.8 / 995
- 5500-6000
- 2 valves per cylinder, single overhead cam (SOHC)
- 18 amp / 226 watt
- Unleaded 90RON minimum
- Mercury FourStroke 25W40 Marine Oil
- SmartCraft Engine Guardian
- Yes
- Electric (turn-key)
- Big Tiller Compatible
- Remote
- Tiller Kit
- 20" / 508 mm
- 1.83:1 or 2.33:1 (CT model)
- 112 kg
- 3
- 2.56 x 2.95" / 65 x 75 mm
- ECM 07 Digital Inductive (CT model)
- ECM 70
- Electronic Fuel Injection (EFI)
- Water-cooled with thermostat
- F-N-R
- Command Thrust (CT)
- Standard
- Power Trim
- Through prop
- 20
- Yes
- Phantom Black
- Wet sump