



Mercury Outboard Motor Specification

Model: Four Stroke 60hp EFI

Matches the acceleration and fuel efficiency of a competitor's more expensive 70hp outboard model

HP/kW

Engine type

Displacement (CID/CC)

Full throttle RPM

Fuel induction system

Alternator amp / Watt Recommended fuel Recommended oil

Engine protection operator warning

system

Compatible with SmartCraft digital

technology

Starting

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition

Fuel system
Cooling system
Gear shift

Gearcase options

Trim system Exhaust system

Shallow water trim range (degrees)

Remote fuel tank (optional)

Color

Lubrication system

- 60 / 44.1
- Inline 4
- 60.8 / 995
- 5500-6000
- 2 valves per cylinder, single overhead cam (SOHC)
- 18 amp / 226 watt
- Unleaded 90RON minimum
- Mercury FourStroke 25W40 Marine Oil
- SmartCraft Engine Guardian
- Yes
- Electric (turn-key)
- Big Tiller Compatible
- Remote
- Tiller Kit
- 20" / 508 mm
- 25" / 635 mm (CT model)
- 1.83:1 or 2.33:1 (CT model)
- 112 kg
- 3
- 2.56 x 2.95" / 65 x 75 mm
- ECM 07 Digital Inductive (CT model)
- ECM 70
- Electronic Fuel Injection (EFI)
- Water-cooled with thermostat
- F-N-R
- Command Thrust (CT)
- Standard
- Power Trim
- Through prop
- 20
- Yes
- Phantom Black
- Wet sump