



Mercury Outboard Motor Specification

Model: Four Stroke 80hp EFI

Re-energize your boat with improved acceleration, performance and manoeuvrability.

HP/kW

Engine type

Displacement (L)

Full throttle RPM

Air induction

Fuel induction system

Alternator amp / Watt

Recommended fuel Recommended oil

Engine protection operator warning

system

Compatible with SmartCraft digital

technology

Starting

Controls

Steering

Shaft length Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition

Fuel system

Cooling system

Gear shift

Gearcase options

Trim system

Exhaust system

Shallow water trim range (degrees)

Color

Lubrication system

Oil Capacity

Maximum Trim Range Maximum Tilt Range • 80/59.2

• 8-valve single overhead cam (SOHC)

Inline 4

• 2.1

4500-5500

Performance-Tuned Scroll Intake Manifold

Computer Controlled Multi-Port Electronic Fuel

Injection (EFI)

35 amp / 441 watt with water-cooled voltage

regulator

Unleaded 90RON minimum

Mercury FourStroke Oil 10W-30

SmartCraft Engine Guardian

Yes

Smart Start Electric

Mechanical throttle & shift

Big Tiller Compatible

Dual cable mechanical

• Hydraulic power steering

20" / 508 mm

• 2.07:1

163 kg

• 3

• 3.5 x 3.2" / 90 x 81 mm

SmartCraft ECM 70 Digital Inductive

• Electronic Fuel Injection (EFI)

Water-cooled with thermostat

• F-N-R

Standard

Power Tilt

Power Trim

Through prop

• 20

Phantom Black

Wet sump

5.5 qts / 5.2 l

• 22° (-6° to 16°)

• 70° (-6° to 64°)