



Mercury Outboard Motor Specification Model: Four Stroke 100hp EFI

Re-energize your boat with improved acceleration, performance and manoeuvrability.

HP/kW

Engine type

Displacement (L)
Full throttle RPM
Air induction

Fuel induction system

Alternator amp / Watt

Recommended fuel Recommended oil

Engine protection operator warning system

Compatible with SmartCraft digital

technology Starting

Controls

Steering

Shaft length

Gearcase ratio

Dry weight *Lightest model available

CARB star rating Bore and stroke

Ignition
Fuel system
Cooling system
Gear shift

Gearcase options

Trim system

Exhaust system

Shallow water trim range (degrees)

Color

Lubrication system

Oil Capacity

Maximum Trim Range
Maximum Tilt Range

100 / 74

• 8-valve single overhead cam (SOHC)

• Inline 4

• 2.1

• 5000-6000

Performance-Tuned Scroll Intake Manifold

 Computer Controlled Multi-Port Electronic Fuel Injection (EFI)

35 amp / 441 watt with water-cooled voltage regulator

Unleaded 90RON minimum

Mercury FourStroke Oil 10W-30

SmartCraft Engine Guardian

Yes

Smart Start Electric

Mechanical throttle & shift

• Big Tiller Compatible

• Dual cable mechanical

Hydraulic power steering

• 20" / 508 mm

25" / 635 mm

2.07:1

163 kg

• 3

• 3.5 x 3.2" / 90 x 81 mm

SmartCraft ECM 70 Digital Inductive

• Electronic Fuel Injection (EFI)

Water-cooled with thermostat

F-N-R

Standard

Power Tilt

Power Trim

Through prop

20

Phantom Black

Wet sump

5.5 qts / 5.2 l

22° (-6° to 16°)

• 70° (-6° to 64°)