This light, compact and easy to handle Nilfisk high-pressure washer is ideal for basic garden cleaning. It offers a maximum pressure of 120 bar - which is enough to be efficient on light to modarately dirty surfaces. The automatic start/stop system along with an aluminum pump makes this a reliable product. Perfect for occasional cleaning of your small to medium sized patio, fence or other surfaces up to 30 m2/ hour.

A handy helper for car, bike or garden furniture washing. Is easy to stow away and offers convenient storage of nozzles, lance and spray handle on the machine.

To increase performance, this Nilfisk comes with Click&Clean connectivity for a range of optional accessories.

- 120 bar max pressure.
- Aluminum pump for high durability.
- Handles mildly dirty surfaces up to 30 m2/ hour.
- Choice of Tornado PR (pressure regulation) or Powerspeed (high impact) nozzles.
 - 6m high-pressure hose.
- Click&Clean connectivity for accessories.
- Compact and easy to use, move around and store.
- The X-TRA model features a built-in trolley for increased mobility.



Picture shown may not represent model quoted

 Standard e 	equipment
--------------------------------	-----------

			Min.		TITAN X-TRA	C 120.7-6 PC	
	Included accessories Ref. no. Ref. no. C 120.7-6 EU UK						
Hose and Connection							
-	G1 GUN NILFISK	128500908	0	•	•	•	
Q	HOSE 6M	126481138	0	•	•	•	
Nozzle - High	Pressure Washer			1			
	PR TORNADO DARK BLUE	126481120	0	•	•	•	
Ą	Wide Angled Auto & Cycle Nozzle	6411136	0		•		
Brush							
-	FIXED BRUSH SHORT NILFISK SP	128500685	0				



	Included accessories	Ref. no.	Min. required	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU
	ROTARY BRUSH	126411395	0		•	
Accessory					1	
	CLEANING TOOL BLACK	6520844	0			
٢	Compact patio	128500700	0		•	•
	DRAIN AND TUBE 8M	128500461	0			
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
5	G2 C&C SPRAY LANCE	128500073	0	•	•	•
	Under Chassis Spray Lance	6410763	0		•	

Standard equipment

	Ref. no.	Min. required	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU			
Hose and Connection								
	G1 GUN NILFISK	128500908	0	•	•	•		
Q	HOSE 6M	126481138	0	•	•	•		
Nozzle - High	Pressure Washer							
	PR TORNADO DARK BLUE	126481120	0	•	•	•		



	Included accessories	Ref. no.	Min. required	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU
	Wide Angled Auto & Cycle Nozzle	6411136	0			
Brush						
	FIXED BRUSH SHORT NILFISK SP	128500685	0	•	•	•
	ROTARY BRUSH	126411395	0			
Accessory						
	CLEANING TOOL BLACK	6520844	0			
٢	Compact patio	128500700	0	•	•	•
	DRAIN AND TUBE 8M	128500461	0		•	
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
	G2 C&C SPRAY LANCE	128500073	0	•	•	•
)	Under Chassis Spray Lance	6410763	0			

Standard equipment

	Included accessories	Ref. no.	Min. required	C 120.7-6 PCAD UK	C 120.7-6 - UK		
Hose and Co	Hose and Connection						
	G1 GUN NILFISK	128500908	0	•	•		



	Included accessories	Ref. no.	Min. required	C 120.7-6 PCAD UK	C 120.7-6 - UK
Q	HOSE 6M	126481138	0	•	•
Nozzle - High	Pressure Washer				
	PR TORNADO DARK BLUE	126481120	0	•	•
Ą	Wide Angled Auto & Cycle Nozzle	6411136	0		
Brush					
	FIXED BRUSH SHORT NILFISK SP	128500685	0	•	
	ROTARY BRUSH	126411395	0		
Accessory					
	CLEANING TOOL BLACK	6520844	0		
٢	Compact patio	128500700	0	•	
	DRAIN AND TUBE 8M	128500461	0	•	
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•
	G2 C&C SPRAY LANCE	128500073	0	•	•
]	Under Chassis Spray Lance	6410763	0		



Model	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU
Ref. no.	128470930	128470946	128471007
PRODUCT FEATURES			
Trolley	•	•	•
Hose reel		•	
Aluminium pump	•	•	•
Lance and spray gun storage	•	•	•
Storage of accessories	•	•	•
Cable storage	•	•	•
Click&Clean (C&C) nozzle concept	•	•	•
Gun with quick connection and swivel	•	•	•
Automatic start/stop	•	•	•
Soft grip			
Hose and cable holder	•	•	•
Telescopic handle			
Wireless PowerGrip			
Pressure regulation in nozzle	•	•	•
Model	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU

Ref. no.	128471008	128471010	128471011
PRODUCT FEATURES			
Trolley	•	•	•
Hose reel			
Aluminium pump	•	•	•
Lance and spray gun storage	•	•	•
Storage of accessories	•	•	•
Cable storage	•	•	•
Click&Clean (C&C) nozzle concept	•	•	•
Gun with quick connection and swivel	•	•	•
Automatic start/stop	•	•	•
Soft grip			
Hose and cable holder	•	•	•
Telescopic handle			
Wireless PowerGrip			
Pressure regulation in nozzle	•	•	•



Ref. no.12847101412847082PRODUCT FEATURESTrolley•••Holes rel·••Aluminium pump••••Storage of accessories·•••Cable storage·•••Cable storage··••Cable storage··••Cable storage··••Cable storage··••Cable storage··••Cable storage··••Automatic start/stop··••Soft grip···•Hoes and cable holder··••Telescopic handle···•Wireless PowerGrip···•Pump pressure (sar/MPa)Max 120 / Max 12Max 120 / Max 12Max 120 / Max 12Rated power (kW)141414Vater flow Camac/Disc (hth)···Alber Ingh (mi)····Sole storgh (mi)····Cable length (mi)····Cable length (mi)····Cable length (mi)····Cable length (mi)····Cable length (mi)····Cable length (mi) </th <th>Model</th> <th></th> <th>C 120.7-6 PCAD UK</th> <th>C 120.7-6 - UK</th>	Model		C 120.7-6 PCAD UK	C 120.7-6 - UK
Tolley • • Hose rel . . Auminium pump . . . Storage of accessories . . . Storage of accessories . . . Cable storage . . . Cable storage of accessories . . . Cable storage of accessories Cable storage of accessories .<	Ref. no.		128471014	128470932
Hourinium pump	PRODUCT FEATURES			
Auminium pump • • Lance and spray gun slorage • • Storage of accessories • • Cable storage • • Click&Clean (C&C) nozzle concept • • Cluck and total storage • • Automatic startstop • • Soft grip • • Hose and cable holder • • Telescopic handle • • Wireless PowerGrip • • Pump pressure regulation in nozzle • • Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/-/Hz/A) 200 -	Trolley		•	•
Lance and spray gun storage Storage of accessories Cable storage Cable st	Hose reel			
Storage of accessories . . Cable storage . . Click&Clean (C&C) nozzle concept . . Gun with quick connection and swivel . . Automatic start/stop . . Soft grip . . . Hose and cable holder . . . Telescopic handle . . . Wireless PowerGrip . . . Pump pressure (bar/MPa) Max 120/Max12 Max 120/Max12 Max 120/Max12 Rated power (kW) Voltage/phase/frequency/current (V/-/Hz/A) 220 - 240 / 1 - / 50 / 52 . . Voltage/phase/frequency/current (V/-/Hz/A) Voltage/phase/frequency/current (V/-/Hz/A) Voltage/phase/frequency/current (V/-/Hz/A) Katch power (kW) Voltage/phase/frequency/current (V/-/Hz/A) 	Aluminium pump		•	•
Cabe sorage • • Click&Clean (C&C) nozzle concept · · Gun with quick connection and swivel · · Automatic start/stop · · Soft grip · · · Hose and cable holder · · · Vireless PowerGrip · · · Pump pressure gulation in nozzle · · · Yotages/PowerGrip Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Atted power (kW) 1.4 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1 / 50 / 6.2 20 - 240 / 1 / 50 / 6.2 20 - 240 / 1 / 50 / 6.2 Water flow Omax/Qice (th) 440 / 310 440 / 310 440 / 310 440 / 310 Vater flow Omax/Qice (th) 6.2 5 5 5 5 Max indict memperature (°C) 40 40 40 40 40 Length x width x height (om) 6.2 6.2 6.2 6.2 6.2	Lance and spray gun storage		•	•
Click&Clean (C&C) nozzle concept • • Gun with quick connection and swivel • • Automatic start/stop • • Soft grip • • Hose and cable holder • • Telescopic handle • • Wireless PowerGrip • • Pressure regulation in nozzle • • Technical specifications C 120.7-6 EU Max 120 / Max 12 Max 120 / Max 12 Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Votage/phase/frequency/current (V/-/Hz/A) 220 - 220 / 12 / 50 / 220 - 240 / 1 / 50 / 220 - 260 / 2 / 20 / 20 / 20 / 20 / 20 / 20 /	Storage of accessories		•	•
Gun with quick connection and swivel • • Automatic start/stop • • Soft grip • • Hose and cable holder • • Telescopic handle · • Wireless PowerGrip · • Pressure regulation in nozzle • • Technical specifications C 120.7-6 EU TRAN X-TRA UK C 120.7-6 PC EU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Votage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 220 - 240 / 1-750 / 250 × 71 Water flow Qmax/Qiec (l/h) 440 / 310 440 / 310 440 / 310 Kase length (m) 6 6 6 6 6 Max. inlet temperature (*C) 40 40 40 40 40 40 40 40 40 40 <td< td=""><td>Cable storage</td><td></td><td>•</td><td>•</td></td<>	Cable storage		•	•
Automatic start/stop • • Soft grip Hose and cable holder • • Telescopic handle · · Wireless PowerGrip · · Technical specifications C120.76 EU TITAN X-TRA UK C120.76 PC U Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~/ 50 / 6.2 220 - 240 / 1~/ 50 / 6.2 220 - 240 / 1~/ 50 / 6.2 Water flow Omax/Qice (l/h) 1.4 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 6 6 6 6 Max. inlet temperature (°C) 440 / 310 440 / 310 440 / 310 440 / 310 400 40	Click&Clean (C&C) nozzle concept		•	•
Sch grip - - Hose and cable holder - - Telescopic handle - - Wireless PowerGrip - - Pressure regulation in nozzle - - Technical specifications C 120.76 EU TITAN X-TRA UK C 120.76 PC EU Nump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1 - / 50 / 6.2 220 - 240 / 1 - / 50 / 6.2 Water flow Qmax/Qiec (l/h) 440 / 310 440 / 310 440 / 310 Valee length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Veight (kg) 6.2 6.4 6.2 Veight (kg) 6.2 6.4 6.2 Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Nat 102 / Max 12 Max 102 / Max 12 Max 120 / Max 12 Veight (kg) 6.2 6.4 6.2 Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 <	Gun with quick connection and swivel		•	•
Hose and cable holder • • Telescopic handle Wireless PowerGrip • • Pressure regulation in nozzle • • • Technical specifications C 120.7-6 EU TITAN X-TRA UK C 120.7-6 PC EU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1 - / 50 / 6.2 20 - 240 / 1 - / 50 / 6.2 Water flow Qmax/Qiec (l/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 6 6 6 Max. inlet temperature (*C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Pump pressure (bar/MPa) Max 120 / Max 12 Max120 / Max 12 Pump pressure (bar/MPa) Max 120 / Max 12 Max120 / Max 12 Voltage/phase/frequency/current (V/~/Hz/A) 26 x 29.5 x 71 26 x 29.5 x 71 Vale flow Qmax/Qiec (l/h) <td>Automatic start/stop</td> <td></td> <td>•</td> <td>•</td>	Automatic start/stop		•	•
Telescopic handle Wireless PowerGrip Pressure regulation in nozzle • Technical specifications C 120.7-6 EU TITAN X.TRA UK C 120.7-6 PC EU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1 - / 50 / 220 - 260 / 1 - / 50 / 200 / 1 - / 50 / 200 / 1 - / 50 / 200 / 200 / 1 - / 50 / 200 / 200 / 1 - / 50 / 200 / 200 / 1 - / 50 / 200 / 200 / 1 - / 50 / 200 / 200 / 1 - / 50 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 200 / 1 - / 50 / 200 / 200 / 200 / 200 / 200 / 200 / 1 - / 50 / 200 / 2	Soft grip			
Wireless PowerGrip • Pressure regulation in nozzle • • Technical specifications C 120.76 EU ITIAN X-TRA UK C 120.76 PC U Pump pressure (bar/MPa) Max 120 / Max1 2 Max 120 / Max1 2 Max 120 / Max1 2 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/-/Hz/A) 220 - 240 / 1 - / 50 / 6.2 220 - 240 / 1 - / 50 / 6.2 Water flow Qmax/Qiec (l/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 × 29.5 x 71 26 × 29.5 x 71 26 × 29.5 x 71 Weight (kg) 6 6 6 6 Fechnical specifications C 120.7-6 PCAU K C 120.7-6 PCAU K 20 - 240 / 1 - / 50 Pump pressure (bar/MPa) Max 120 / Max1 2 Max 120 / Max1 2 Max 120 / Max1 2 Pump pressure (bar/MPa) Max 120 / Max1 2 Max 120 / Max1 2 Voltage/phase/frequ	Hose and cable holder		•	•
Pressure regulation in nozzle • • Technical specifications C 120.76 EU TITAN X-TRA UK C 120.76 PC EU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (l/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 × 29.5 x 71 26 × 29.5 x 71 26 × 29.5 x 71 Veight (kg) 6 6 6.2 6.2 Fechnical specifications C 120.7-6 PCA UK C 120.7-6 PCA UK 20 × 240 / 1~ / 50 / 6.2 Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A)	Telescopic handle			
Technical specifications C 120.7.6 EU TTAN X.TRA UK C 120.7.6 C U Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/-/Hz/A) 220-240 / 1~/50 / 6.2 220-240 / 1~/50 / 6.2 220-240 / 1~/50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.7-6 PCA UK C 120.7-6 PCA EU C 120.7-6 PCA EU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 120 Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 120 Max 120 / Max 120 Voltage/phase/frequency/current (V/-/Hz/A) 220-240 / 1-/50 / 6.2 6.2 6.2	Wireless PowerGrip			
Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.7-6 PCA UK C 120.7-6 PCA DE U C 120.7-6 PCA EU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 6.2 6.2 6.2 6.2 6.2 6.2 6.2 6.2 6.2 <	Pressure regulation in nozzle		•	•
Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Veight (kg) 6.2 6.4 6.2 Technical specifications C 120.7-6 PCA UK C 120.7-6 PCA DEU C 120.7-6 PCA EU Pump pressure (bar/IMPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 6.2 20 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (l/h) 400 400 400 300 6.2 Voltage/phase/frequency/current (V/~/Hz/A) 6.2 5 <t< td=""><td>Technical specifications</td><td>C 120.7-6 EU</td><td>TITAN X-TRA UK</td><td>C 120.7-6 PC EU</td></t<>	Technical specifications	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU
Voltage/phase/frequency/current (V/~/Hz/A) $220 - 240 / 1 - 750 / 6.2$ $220 - 240 / 1 - 750 / 6.2$ $220 - 240 / 1 - 750 / 6.2$ Water flow Qmax/Qiec (I/h)440 / 310440 / 310440 / 310440 / 310Cable length (m)555Hose length (m)666Max. inlet temperature (°C)404040Length x width x height (cm)26 x 29.5 x 7126 x 29.5 x 7126 x 29.5 x 71Weight (kg)6.26.46.2Technical specificationsC 120.7-6 PCA UKC 120.7-6 PCA DEUC 120.7-6 PCA EUPump pressure (bar/MPa)Max 120 / Max 12Max 120 / Max 12Max 120 / Max 12Rated power (kW)1.41.41.4Voltage/phase/frequency/current (V/~/Hz/A) $220 - 240 / 1 - 750 / 6.2$ $220 - 240 / 1 - 750 / 6.2$ Water flow Qmax/Qiec (I/h)440 / 310440 / 310440 / 310Cable length (m)555Hose length (m)666	Pump pressure (bar/MPa)	Max 120 / Max 12	Max 120 / Max 12	Max 120 / Max 12
Voltage/phase/requency/current (V/~/H2/A) 6.2 6.2 6.2 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.76 PCA UK C 120.76 PCA DEU C 120.76 PCA DEU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 20 - 240 / 1~ / 50 / 6.2 20 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Voltage/phase/frequency/current (V/~/Hz/A) 5 5 5 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310	Rated power (kW)	1.4	1.4	1.4
Cable length (m) 5 5 Hose length (m) 6 6 6 Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.7 6 PCA UK C 120.7 6 PCA DEU C 120.7 6 PCA DEU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1 ~ / 50 / 6.2 5 5 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Gable length (m) 5 5 5 Hose length (m) 6 6 6	Voltage/phase/frequency/current (V/~/Hz/A)			
Hose length (m)666Max. inlet temperature (°C)404040Length x width x height (cm)26 x 29.5 x 7126 x 29.5 x 7126 x 29.5 x 71Weight (kg)6.26.46.2Technical specificationsC 120.7-6 PCA UKC 120.7-6 PCA DEUC 120.7-6 PCA EUPump pressure (bar/MPa)Max 120 / Max 12Max 120 / Max 12Max 120 / Max 12Rated power (kW)1.41.41.4Voltage/phase/frequency/current (V/~/Hz/A)200 - 240 / 1~ / 50 / 6.220 - 240 / 1~ / 50 / 6.2Water flow Qmax/Qiec (l/h)440 / 310440 / 310440 / 310Lable length (m)555Hose length (m)666	Water flow Qmax/Qiec (I/h)	440 / 310	440 / 310	440 / 310
Max. inlet temperature (°C) 40 40 40 Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.76 PCA UK C 120.76 PCA DEU C 120.76 PCA DEU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 202 - 240 / 1~ / 50 / 6.2 202 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Hose length (m) 5 5 5 Hose length (m) 6 6 6	Cable length (m)	5	5	5
Length x width x height (cm) 26 x 29.5 x 71 26 x 29.5 x 71 26 x 29.5 x 71 Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.7-6 PCA UK C 120.7-6 PCA DEU C 120.7-6 PCA DEU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 20 - 240 / 1~ / 50 / 6.2 20 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Hose length (m) 6 6 6	Hose length (m)	6	6	6
Weight (kg) 6.2 6.4 6.2 Technical specifications C 120.7-6 PCA UK C 120.7-6 PCA DEU C 120.7-6 PCA DEU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (l/h) 440 / 310 440 / 310 440 / 310 Hose length (m) 5 5 5 Hose length (m) 64 6 6	Max. inlet temperature (°C)	40	40	40
Technical specifications C 120.7-6 PCA UK C 120.7-6 PCA DEU C 120.7-6 PCA DEU Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6	Length x width x height (cm)	26 x 29.5 x 71	26 x 29.5 x 71	26 x 29.5 x 71
Pump pressure (bar/MPa) Max 120 / Max 12 Max 120 / Max 12 Max 120 / Max 12 Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6	Weight (kg)	6.2	6.4	6.2
Rated power (kW) 1.4 1.4 1.4 Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6	Technical specifications	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU
Voltage/phase/frequency/current (V/~/Hz/A) 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 220 - 240 / 1~ / 50 / 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6	Pump pressure (bar/MPa)	Max 120 / Max 12	Max 120 / Max 12	Max 120 / Max 12
Voltage/phase/inequency/current (V/-/H2/A) 6.2 6.2 6.2 Water flow Qmax/Qiec (I/h) 440 / 310 440 / 310 440 / 310 Cable length (m) 5 5 5 Hose length (m) 6 6 6	Rated power (kW)	1.4	1.4	1.4
Cable length (m) 5 5 5 Hose length (m) 6 6 6	Voltage/phase/frequency/current (V/~/Hz/A)			
Hose length (m) 6 6 6	Water flow Qmax/Qiec (I/h)	440 / 310	440 / 310	440 / 310
	Cable length (m)	5	5	5
Max. inlet temperature (°C) 40 40 40	Hose length (m)	6	6	6
	Max. inlet temperature (°C)	40	40	40



Technical specifications	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU
Length x width x height (cm)	26 x 29.5 x 71	26 x 29.5 x 71	26 x 29.5 x 71
Weight (kg)	6.2	6.2	6.2
Technical specifications		C 120.7-6 PCAD UK	C 120.7-6 - UK
Pump pressure (bar/MPa)		Max 120 / Max 12	Max 120 / Max 12
Rated power (kW)		1.4	1.4
Voltage/phase/frequency/current (V/~/Hz/A)		220 - 240 / 1~ / 50 / 6.2	220 - 240 / 1~ / 50 / 6.2
Water flow Qmax/Qiec (I/h)		440 / 310	440 / 310
Cable length (m)		5	5
Hose length (m)		6	6
Max. inlet temperature (°C)		40	40
Length x width x height (cm)		26 x 29.5 x 71	26 x 29.5 x 71
Weight (kg)		6.2	6.2

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU	
Hose and Connection							
Q	EXT. HOSE 7 M - QUICK COUPLING	106411346	0	0	0	0	
\bigcirc	Extension Hose	6410760	0	0	0	0	
0	EXTENSION HOSE STEEL ARMED 7 M	6411048	0	0	0	0	
-7	G1 GUN NILFISK	128500908	0	•	•	•	
Q	HOSE 6M	126481138	0	•	•	•	
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0	
Brush							



	Accessories	Ref. no.	Min. required	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU
	Auto brush	6411131	0	0	0	0
•	Car brush head	128500463	0	0	0	0
-	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	0
-	Garden brush head	128470457	0	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0	0
	ROTARY BRUSH	6410762	0	0	0	0
	ROTARY BRUSH	126411395	0	0	•	0
Accessory		1				
	CLEANING TOOL BLACK	6520844	0	0	0	0
	Compact patio	128500700	0	0	•	•
<u>,</u>	DRAIN AND TUBE 8M	128500461	0	0	0	0
\bigcirc	DRAIN AND TUBE CLEANER 15M	6410766	0	0	0	0
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•



	Accessories	Ref. no.	Min. required	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU		
ii an	G2 C&C SPRAY LANCE	128500073	0	•	•	•		
	INLET SUCTION HOSE 3M	128500673	0	0	0	0		
	MULTI ANGLE ADAPTER	6411138	0	0	0	0		
ä	MULTI BRUSH	128470456	0	0	0	0		
-F -	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0		
	NILFISK POWER PATIO	128500955	0	0	0	0		
	NILFISK WATER FILTER	128500674	0	0	0	O		
1	Patio Cleaner	128500702	0	O	O	0		
с. 4.	ROOF CLEANER	128470040	0	0	0	0		
	Under Chassis Spray Lance	6410763	0	0	•	0		
	VSB SET - GREEN	6410891	0	0	0	O		
~ "	Water Emptying Kit	126411387	0	0	0	0		
Nozzle - High	Nozzle - High Pressure Washer							



	Accessories	Ref. no.	Min. required	C 120.7-6 EU	TITAN X-TRA UK	C 120.7-6 PC EU
	PR TORNADO DARK BLUE	126481120	0	•	•	•
ļ	Under Chassis Nozzle	6411135	0	0	0	0
Ą	Wide Angled Auto & Cycle Nozzle	6411136	0	0	●	0
Accessory Kit						
	MULTI BRUSH KIT	128470459	0	0	0	0
•• 000 0	O-RING KIT CONSUMER HPW	128500292	0	0	0	0

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU		
Hose and Co	Hose and Connection							
Ø	EXT. HOSE 7 M - QUICK COUPLING	106411346	0	0	0	0		
Q	Extension Hose	6410760	0	0	0	0		
0	EXTENSION HOSE STEEL ARMED 7 M	6411048	0	0	0	0		
	G1 GUN NILFISK	128500908	0	•	•	•		
Q	HOSE 6M	126481138	0	•	•	•		



Pressure washers

C 120.7/ C 120.7 X-TRA

	Accessories	Ref. no.	Min. required	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU	
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0	
Brush							
	Auto brush	6411131	0	0	0	0	
0	Car brush head	128500463	0	0	0	0	
	FIXED BRUSH SHORT NILFISK SP	128500685	0	•	•	•	
	Garden brush head	128470457	0	0	0	0	
	RIM BRUSH HEAD	128470458	0	O	0	0	
	ROTARY BRUSH	6410762	0	0	0	0	
	ROTARY BRUSH	126411395	0	0	0	0	
Accessory			1				
	CLEANING TOOL BLACK	6520844	0	0	0	0	
	Compact patio	128500700	0	•	•	•	
<u>,</u>	DRAIN AND TUBE 8M	128500461	0	O	•	0	



	Accessories	Ref. no.	Min. required	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU
\bigcirc	DRAIN AND TUBE CLEANER 15M	6410766	0	0	0	0
	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
	G2 C&C SPRAY LANCE	128500073	0	•	•	•
	INLET SUCTION HOSE 3M	128500673	0	0	0	0
	MULTI ANGLE ADAPTER	6411138	0	0	0	0
(ana)	MULTI BRUSH	128470456	0	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0
	NILFISK POWER PATIO	128500955	0	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0	0
(Patio Cleaner	128500702	0	0	0	0
d	ROOF CLEANER	128470040	0	0	0	0
	Under Chassis Spray Lance	6410763	0	0	0	0



	Accessories	Ref. no.	Min. required	C 120.7-6 PCA UK	C 120.7-6 PCAD EU	C 120.7-6 PCA EU
	VSB SET - GREEN	6410891	0	0	0	0
6 ,	Water Emptying Kit	126411387	0	0	0	0
Nozzle - High	Pressure Washer					
	PR TORNADO DARK BLUE	126481120	0	•	•	•
4	Under Chassis Nozzle	6411135	0	0	0	0
Ą	Wide Angled Auto & Cycle Nozzle	6411136	0	0	0	0
Accessory Kit		·				
	MULTI BRUSH KIT	128470459	0	0	0	0
•• 000	O-RING KIT CONSUMER HPW	128500292	0	0	0	0

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	C 120.7-6 PCAD UK	C 120.7-6 - UK
Hose and Co	nnection				
Ø	EXT. HOSE 7 M - QUICK COUPLING	106411346	0	0	0
\mathbf{O}	Extension Hose	6410760	0	0	0
0	EXTENSION HOSE STEEL ARMED 7 M	6411048	0	0	0



	Accessories	Ref. no.	Min. required	C 120.7-6 PCAD UK	C 120.7-6 - UK
	G1 GUN NILFISK	128500908	0	•	•
Q	HOSE 6M	126481138	0	•	•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0
Brush					
	Auto brush	6411131	0	0	0
0	Car brush head	128500463	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	•	o
	Garden brush head	128470457	0	0	0
	RIM BRUSH HEAD	128470458	0	o	o
	ROTARY BRUSH	6410762	0	o	o
	ROTARY BRUSH	126411395	0	0	o
Accessory					
	CLEANING TOOL BLACK	6520844	0	0	0



	Accessories	Ref. no.	Min. required	C 120.7-6 PCAD UK	C 120.7-6 - UK
٢	Compact patio	128500700	0	•	0
	DRAIN AND TUBE 8M	128500461	0	•	0
\bigcirc	DRAIN AND TUBE CLEANER 15M	6410766	0	0	0
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•
iz	G2 C&C SPRAY LANCE	128500073	0	•	•
	INLET SUCTION HOSE 3M	128500673	0	0	0
, (1000)	MULTI ANGLE ADAPTER	6411138	0	0	0
una -	MULTI BRUSH	128470456	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0
	NILFISK POWER PATIO	128500955	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0
•	Patio Cleaner	128500702	0	0	0



	Accessories	Ref. no.	Min. required	C 120.7-6 PCAD UK	C 120.7-6 - UK
d.L	ROOF CLEANER	128470040	0	0	0
	Under Chassis Spray Lance	6410763	0	0	0
	VSB SET - GREEN	6410891	0	0	0
°	Water Emptying Kit	126411387	0	0	0
Nozzle - High	Pressure Washer				
	PR TORNADO DARK BLUE	126481120	0	•	•
Ļ	Under Chassis Nozzle	6411135	0	o	0
	Wide Angled Auto & Cycle Nozzle	6411136	0	0	0
Accessory Kit					
	MULTI BRUSH KIT	128470459	0	0	0
•• 000	O-RING KIT CONSUMER HPW	128500292	0	0	0

